



QP1680 High-Temperature TNb Laboratory Analyser, with auto sampler, 65 positions

Αρ. προϊόντος:

LPV448.99.02001

EUR Τιμή:

Επικοινωνήστε μαζί μας

Δεν εμφανίζεται η ημερομηνία αποστολής

The QP1680 is available as a combined TOC and TN_b analyser or for the individual parameters TOC or TN_b.

The most important features include:

- Direct sample injection eliminates sample contact with valves and the built-in injection syringe, which minimizes the risk of sample carry-over.
- Large diameter sample aspiration tubing can handle particles up to 800 µm, expanding possible applications and reducing clogging.
- Integrated stirrer for each sample position homogenizes particle-containing samples before injection.
- Small footprint with integrated 65-position auto-sampler requires less space in the laboratory (an auto-sampler with 96 positions is also available as an alternative).
- Simple operation, data analysis and system diagnosis thanks to an intuitive software package.

Προδιαγραφές

Analysis time:	Approx. 3 minutes
Gas consumption:	200 mL/min
Gas specifications:	Oxygen or synthetic air: minimum 99.998% (4.8) at 3 - 10 bar
Number of sample positions:	65
Oxidation method:	Catalytic combustion at 720 °C
Βαθμός μόλυνσης :	2
Βάρος :	Approx. 29 kg
Διαστάσεις:	440 mm x 380 mm x 700 mm (H x W x D)
Εγγύηση :	24 μήνες
Επαναληψιμότητα :	Up to 10 mg/L TC, TIC, NPOC, TN: < 5% > 10 mg/L TC, TIC, NPOC, TN: < 2%
Εύρος μέτρησης :	TN _b : 0 - 30000 mg/L
Ηλεκτρική τροφοδοσία:	Analyser: 100 - 240 VAC, 50/60 Hz, 16 A, with protective grounding PC: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding Monitor: 100 - 240 VAC, 50/60 Hz, 1.6 A, with protective grounding
Θερμοκρασία :	Furnace temperature max. 1050 °C (depending on configuration)
Θερμοκρασία περιβάλλοντος :	-20 - 60 °C

Μέθοδος μέτρησης :	Chemiluminescence
Μοντέλο :	QP1680-TN _b
Νόρμες και Πρότυπα :	TN _b : ASTM D8083, EN 12260, ISO 11905-2, NEN-ISO 20236
Όγκος δείγματος :	10 - 1000 µL
Όριο ανίχνευσης :	TN: 20 µg/L
Παράμετρος :	TN _b
Συνθήκες λειτουργίας :	20 - 30 °C; 20 - 80% relative humidity (non-condensing)
Τι περιέχει το καλάθι:	TN _b Instrument
	Sample tray with 65 positions for 40 mL vials
	Glass sample vials 40 mL (100 pcs)
	USB 2.0 cable A-B
	Set of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferrule
	Reagent container with screwcap for UPW, Acid and Waste
	Power cord
	USB storage device with software, test results and Full User Manual
	Printed User Manual
τροφοδοσία :	Analyser: 750 W max.
	PC: 90 W max.
	Monitor: 100 W max.

Τι περιέχει το καλάθι

TN_b InstrumentSample tray with 65 positions for 40 mL vialsGlass sample vials 40 mL (100 pcs)USB 2.0 cable A-BSet of tubing PTFE blue-stripe 1/8" OD length 2 m including nut & ferruleReagent container with screwcap for UPW, Acid and WastePower cordUSB storage device with software, test results and Full User ManualPrinted User Manual

Απαιτούμενα παρελκόμενα

- QP1680 TOC/TN_b Starter Package (Item SMKIT500000)