

Sension+ 5070 Universal conductivity electrode for lab use

Αρ. προϊόντος: **LZW5070.97.0002**

EUR Τιμή:
Διαθέσιμο

Επικοινωνήστε μαζί μας

Conductivity cell with Pt electrodes and glass body for Sension+ benchtop meters. Cell constant k=1 cm^{-1}. Built-in Pt1000 for automatic temperature compensation. 1 m cable.

Measuring range 0.2 µS/cm - 200 mS/cm, 0 - 80 °C.

The electrode is suitable for general aqueous applications.

Built in Pt1000 for automatic temperature compensation.

Προδιαγραφές

Accuracy:	0.50% EC & TDS
Electrode junction :	-
Διάλυμα πλήρωσης :	-
Διαστάσεις (BxM):	12 mm x 130 mm
Εγγύηση :	12 μήνες
Εύρος θερμοκρασίας :	0 - 80 °C
Εύρος μέτρησης :	0,2 µS/cm - 200 mS/cm
Θερμική αντίσταση :	Pt1000
Μήκος :	130 mm
Μήκος καλωδίου :	1 m
Παράμετρος :	Conductivity
Σύνδεσμος :	RJ45 (phone)
Τύπος :	Εργαστήριο
Τύπος αισθητηρίου :	3-pole Platinum, k = 0.7 cm^{-1}
Τύπος ηλεκτροδίων :	Laboratory
Υλικό :	Sensor Body Outside: Polycarbonate, Inside: Glass, Sensor Cell: Platinum